

Series SEC

(Stepless Ear Clamps)



- Material: Stainless steel 304
- Non-spill: Complete clamping 360 degree
- Non-releasing: Clamping forever
- Auto-compensation when temperature change
- Radius band edge: Clamping protection



Part Number	Size Range	Ear Width	Clamping Force	Part Number	Size Range	Ear Width	Clamping Force
Band Width: 5mm, Band Thickness: 0.5mm				Band Width: 7mm, Band Thickness: 0.6mm			
SEC 065	5.3-6.5	4	1000N	SEC 160	13.5-16.0	8	2100N
SEC 070	5.8-7.0	4	1000N	SEC 162	13.7-16.2	8	2100N
SEC 080	6.8-8.0	4	1000N	SEC 166	14.1-16.6	8	2100N
SEC 087	7.0-8.7	5.5	1000N	SEC 168	14.3-16.8	8	2100N
SEC 090	7.3-9.0	5.5	1000N	SEC 170	14.5-17.0	8	2100N
SEC 095	7.8-9.5	5.5	1000N	SEC 175	15.0-17.5	8	2100N
SEC 100	8.3-10.0	5.5	1000N	SEC 178	14.6-17.8	10	2400N
SEC 105	8.8-10.5	5.5	1000N	SEC 180	14.8-18.0	10	2400N
SEC 109	9.2-10.9	5.5	1000N	SEC 185	15.3-18.5	10	2400N
SEC 113	9.6-11.3	5.5	1000N	SEC 192	16.0-19.2	10	2400N
SEC 118	10.1-11.8	5.5	1000N	SEC 198	16.6-19.8	10	2400N
Band Width: 7mm, Band Thickness: 0.6mm				SEC 210	17.8-21.0	10	2400N
SEC 119	9.4-11.9	8	2100N	SEC 226	19.4-22.6	10	2400N
SEC 123	9.8-12.3	8	2100N	SEC 235	20.3-23.5	10	2400N
SEC 128	10.3-12.8	8	2100N	SEC 241	20.9-24.1	10	2400N
SEC 133	10.8-13.3	8	2100N	SEC 256	22.4-25.6	10	2400N
SEC 138	11.3-13.8	8	2100N	SEC 271	23.9-27.1	10	2400N
SEC 140	11.5-14.0	8	2100N	SEC 286	25.4-28.6	10	2400N
SEC 142	11.7-14.2	8	2100N	SEC 301	26.9-30.1	10	2400N
SEC 145	12.0-14.5	8	2100N	SEC 308	27.6-30.8	10	2400N
SEC 148	12.3-14.8	8	2100N	SEC 316	28.4-31.6	10	2400N
SEC 153	12.8-15.3	8	2100N	SEC 331	29.8-33.1	10	2400N
SEC 157	13.2-15.7	8	2100N	SEC 346	31.4-34.6	10	2400N

Part Number	Size Range	Ear Width	Clamping Force	Part Number	Size Range	Ear Width	Clamping Force
Band Width: 7mm, Band Thickness: 0.6mm				Band Width: 7mm, Band Thickness: 0.6mm			
SEC 361	32.9-36.1	10	2400N	SEC 785	75.3-78.5	10	2400N
SEC 376	34.4-37.6	10	2400N	SEC 800	76.8-80.0	10	2400N
SEC 381	34.9-38.1	10	2400N	SEC 815	78.3-81.5	10	2400N
SEC 396	36.4-39.6	10	2400N	SEC 830	79.8-83.0	10	2400N
SEC 410	37.8-41.0	10	2400N	SEC 845	81.3-84.5	10	2400N
SEC 425	39.3-42.5	10	2400N	SEC 860	82.8-86.0	10	2400N
SEC 440	40.8-44.0	10	2400N	SEC 875	84.3-87.5	10	2400N
SEC 455	42.3-45.5	10	2400N	SEC 890	85.8-89.0	10	2400N
SEC 470	43.8-47.0	10	2400N	SEC 905	87.3-90.5	10	2400N
SEC 485	45.3-48.5	10	2400N	SEC 920	88.8-92.0	10	2400N
SEC 500	46.8-50.0	10	2400N	SEC 935	90.3-93.5	10	2400N
SEC 515	48.3-51.5	10	2400N	SEC 950	91.8-95.0	10	2400N
SEC 530	49.8-53.0	10	2400N	SEC 965	93.3-96.5	10	2400N
SEC 545	51.3-54.5	10	2400N	SEC 980	94.8-98.0	10	2400N
SEC 560	52.8-56.0	10	2400N	SEC 995	96.3-99.5	10	2400N
SEC 575	54.3-57.5	10	2400N	SEC 1010	97.8-101.0	10	2400N
SEC 590	55.8-59.0	10	2400N	SEC 1025	99.3-102.5	10	2400N
SEC 605	57.3-60.5	10	2400N	SEC 1040	100.8-104.0	10	2400N
SEC 620	58.8-62.0	10	2400N	SEC 1055	102.3-105.5	10	2400N
SEC 635	60.3-63.5	10	2400N	SEC 1070	103.8-107.0	10	2400N
SEC 650	61.8-65.0	10	2400N	SEC 1085	105.3-108.5	10	2400N
SEC 665	63.3-66.5	10	2400N	SEC 1100	106.8-110.0	10	2400N
SEC 680	64.8-68.0	10	2400N	SEC 1115	108.3-111.5	10	2400N
SEC 695	66.3-69.5	10	2400N	SEC 1130	109.8-113.0	10	2400N
SEC 710	67.8-71.0	10	2400N	SEC 1145	111.3-114.5	10	2400N
SEC 725	69.3-72.5	10	2400N	SEC 1160	112.8-116.0	10	2400N
SEC 740	70.8-74.0	10	2400N	SEC 1175	114.3-117.5	10	2400N
SEC 755	72.3-75.5	10	2400N	SEC 1190	115.8-119.0	10	2400N
SEC 770	73.8-77.0	10	2400N	SEC 1205	117.3-120.5	10	2400N